

**Base Part Number** QSFP+-SR

## **Product Features**

 Form Factor **QSFP**  Speed 42 Gbps

100m OM3 / 150m OM4 Distance Commercial: 0°C to +70°C

 Operating Temperature Connector Type **MPO-12**  Fiber Type **MMF** 



Brand	Com	pati	bility	/
Diana		Paci	~	,

				_
OEM I	Equival	ent Pa	ırt Num	ber

# **Applications**

- 40G Ethernet and OTU3
- Datacom/Telecom switch & router connections
- Data aggregration and backplane applications
- Proprietary Protocol and Density Applications
- · Infiniband transmission at 4ch SDR, DDR, and

#### **Key Specifications**

Part Type	Max Data Rate	Fiber Type	Transmitter	Output Power	Receiver Sensitivity	Power Supply	Power Dissipation	DDM
QSFP+-SR	10.5 Gbps per lane	MMF	850nm VCSEL	-6.5 to -1dBm	-5.4dBm	3.3V	1.5W	Yes

### Compliance

MSA, SFF-8636

# **Qualifications and Testing**

- Manufacturer: OEM equivalent part; designed, tested, fabricated to supplier specifications following ISO certified processes. RoHS compliant & class 1 laser certified.
- Supplier: 100% compatibility tested in the listed brands.
- Order: All parts are tested for traffic functionality per supported layer 2/3 protocol, DOM/DDM threshold and calibration, EEPROM MSA value verification, serial number verification & optical cleanliness.

#### Warranty

· Lifetime replacement warranty