

Base Part Number SFP+-BX-U40-IND SFP+-BX-D40-IND

Product Features

Form Factor

Speed

Distance

Operating Temperature

Connector Type

Fiber Type

SFP+

11.3 Gbps

40km

Industrial: -40°C to +85°C

Simplex LC

SMF



Brand Compatibility

	_	=	

OEM Equivalent Part Number

Applications

- 10GBASE-BX Ethernet
- 10GBASE-LR at 10.3125 GBps
- 10GBASE-LW at 9.953 GBps
- · CPRI and OBSAI
- 2x/4x/8x Fiber Channel

Key Specifications

Part Type	Max Data Rate	Fiber Type	Transmitter	Output Power	Receiver Sensitivity	Power Supply	Power Dissipation	DDM
SFP+-BX-U40-IND	11.3 Gbps	SMF	1270nm TX/ 1330nm RX	0.5 to 6dBm	-14.5dBm	3.3V	1.2W	Yes
SFP+-BX-D40-IND	11.3 Gbps	SMF	1330nm TX/ 1270nm RX	O.5 to 6dBm	-14.5dBm	3.3V	1.2W	Yes

Compliance

SFF-8431, SFF-8472

Qualifications and Testing

- Manufacturer: OEM equivalent part; designed, tested, fabricated to supplier specifications following ISO certified processes. RoHS compliant & class 1 laser certified.
- Supplier: 100% compatibility tested in the listed brands.
- Order: All parts are tested for traffic functionality per supported layer 2/3 protocol, DOM/DDM threshold and calibration, EEPROM MSA value verification, serial number verification & optical cleanliness.

Warranty

Lifetime replacement warranty