

**Base Part Number**      **SFP28-ESR**

## Product Features

- **Form Factor**                      SFP28
- **Speed**                              25.78 Gbps
- **Distance**                          200M OM3 / 300M OM4
- **Operating Temperature**   Industrial: -40°C to +85°C
- **Connector**                       Duplex LC
- **Fiber Type**                        MMF



## Brand Compatibility

## Applications

- CPRI/eCPRI Option 10
- 25G Ethernet

## OEM Equivalent Part Number

## Key Specifications

Part Type	Max Data Rate	Fiber Type	Transmitter	Output Power	Receiver Sensitivity	Power Supply	Power Consumption	DDM
SFP28-ESR	25.78 Gbps	MMF	850nm VCSEL	-8.4 to +2.4 dBm	-11.9dBm	3.3V	1W	Yes

## Compliance

- SFP+ MSA, SFF-8472

## Qualifications and Testing

- **Manufacturer:** OEM equivalent part; designed, tested, fabricated to supplier specifications following ISO certified processes. RoHS compliant & class 1 laser certified.
- **Supplier:** 100% compatibility tested in the listed brands.
- **Order:** All parts are tested for traffic functionality per supported layer 2/3 protocol, DOM/DDM threshold and calibration, EEPROM MSA value verification, serial number verification & optical cleanliness.

## Warranty

- Lifetime warranty.